2025/06/20 01:21 1/15 Formatting syntax

Formatting syntax

SokuWiki supports some simple markup language, which tries to make the datafiles to be as readable as possible. This page contains all possible syntax you may use when editing the pages. Simply have a look at the source of this page by pressing the Show pagesource button to the right of the page. If you want to try something, just use the playground page. The simpler markup is easily accessible via quickbuttons, too.

Basic text formatting

DokuWiki supports **bold**, *italic*, <u>underlined</u> and monospaced texts. Of course you can <u>combine</u> all these.

```
DokuWiki supports **bold**, //italic//, __underlined__ and ''monospaced'' texts.

Of course you can **__//''combine''//__** all these.
```

You can use _{subscript} and ^{superscript}, too.

You can use _{subscript} and ^{superscript}, too.

You can mark something as deleted as well.

You can mark something as deleted as well.

Paragraphs are created from blank lines. If you want to **force a newline** without a paragraph, you can use two backslashes followed by a whitespace or the end of line.

This is some text with some linebreaks

Note that the two backslashes are only recognized at the end of a line
or followed by
a whitespace \\this happens without it.

This is some text with some linebreaks\\ Note that the two backslashes are only recognized at the end of a line\\ or followed by\\ a whitespace \\this happens without it.

You should use forced newlines only if really needed.

Links

DokuWiki supports multiple ways of creating links.

External

Last update: 2021/03/19 14:27

External links are recognized automagically: http://www.google.com or simply www.google.com - You can set the link text as well: This Link points to google. Email addresses like this one: andi@splitbrain.org are recognized, too.

```
DokuWiki supports multiple ways of creating links. External links are recognized automagically: http://www.google.com or simply www.google.com - You can set link text as well: [[http://www.google.com|This Link points to google]]. Email addresses like this one: <andi@splitbrain.org> are recognized, too.
```

Internal

Internal links are created by using square brackets. You can either just give a pagename or use an additional link text.

```
Internal links are created by using square brackets. You can either just
give
a [[pagename]] or use an additional [[pagename|link text]].
```

Wiki pagenames are converted to lowercase automatically, special characters are not allowed.

You can use namespaces by using a colon in the pagename.

```
You can use [[some:namespaces]] by using a colon in the pagename.
```

For details about namespaces see **namespaces**.

Linking to a specific section is possible, too. Just add the section name behind a hash character as known from HTML. This links to this Section.

```
This links to [[syntax#internal|this Section]].
```

Notes:

- Links to existing pages are shown in a different style from nonexisting ones.
- DokuWiki does not use WCamelCase to automatically create links by default, but this behavior can be enabled in the Sconfig file. Hint: If DokuWiki is a link, then it's enabled.
- When a section's heading is changed, its bookmark changes, too. So don't rely on section linking too much.

Interwiki

DokuWiki supports Interwiki links. These are quick links to other Wikis. For example this is a link to Wikipedia's page about Wikis: WWiki.

2025/06/20 01:21 3/15 Formatting syntax

DokuWiki supports [[doku>Interwiki]] links. These are quick links to other Wikis.
For example this is a link to Wikipedia's page about Wikis: [[wp>Wiki]].

Windows shares

windows snares

Windows shares like this are recognized, too. Please note that these only make sense in a homogeneous user group like a corporate Wintranet.

```
Windows Shares like [[\\server\share|this]] are recognized, too.
```

Notes:

- For security reasons direct browsing of windows shares only works in Microsoft Internet Explorer per default (and only in the "local zone").
- For Mozilla and Firefox it can be enabled through different workaround mentioned in the Mozilla Knowledge Base. However, there will still be a JavaScript warning about trying to open a Windows Share. To remove this warning (for all users), put the following line in conf/lang/en/lang.php (more details at Socalization):

conf/lang/en/lang.php

```
<?php
/**
 * Customization of the english language file
 * Copy only the strings that needs to be modified
 */
$lang['js']['nosmblinks'] = '';</pre>
```

Image links

You can also use an image to link to another internal or external page by combining the syntax for links and images (see below) like this:

```
[[http://php.net|{{wiki:dokuwiki-128.png}}]]
```



Please note: The image formatting is the only formatting syntax accepted in link names.

The whole image and link syntax is supported (including image resizing, internal and external images and URLs and interwiki links).

Footnotes

Last update: 2021/03/19 14:27

You can add footnotes 1) by using double parentheses.

You can add footnotes ((This is a footnote.)) by using double parentheses.

Sectioning

You can use up to five different levels of headlines to structure your content. If you have more than three headlines, a table of contents is generated automatically – this can be disabled by including the string ~~NOTOC~~ in the document.

Headline Level 3

Headline Level 4

Headline Level 5

```
==== Headline Level 3 ====
=== Headline Level 4 ===
== Headline Level 5 ==
```

By using four or more dashes, you can make a horizontal line:

Media files

You can include external and internal **simages**, videos and audio files with curly brackets. Optionally you can specify the size of them.

Real size:

Resize to given width:

Resize to given width and height²⁾: \blacksquare



Resized external image:

```
Real size: {{wiki:dokuwiki-128.png}}
Resize to given width: {{wiki:dokuwiki-128.png?50}}
Resize to given width and height: {{wiki:dokuwiki-128.png?200x50}}
```

2025/06/20 01:21 5/15 Formatting syntax

Resized external image: {{https://php.net/images/php.gif?200x50}}

By using left or right whitespaces you can choose the alignment.

×

×

```
{{ wiki:dokuwiki-128.png}} {{wiki:dokuwiki-128.png }} {{ wiki:dokuwiki-128.png }}
```

×

Of course, you can add a title (displayed as a tooltip by most browsers), too.

{{ wiki:dokuwiki-128.png | This is the caption}}

For linking an image to another page see Image Links above.

Supported media formats

DokuWiki can embed the following media formats directly.

Image	gif, jpg, png
Video	webm, ogv, mp4
Audio	ogg, mp3, wav
Flash	swf

If you specify a filename that is not a supported media format, then it will be displayed as a link instead.

By adding ?linkonly you provide a link to the media without displaying it inline

```
{{wiki:dokuwiki-128.png?linkonly}}
```

dokuwiki-128.png This is just a link to the image.

Fallback formats

Unfortunately not all browsers understand all video and audio formats. To mitigate the problem, you can upload your file in different formats for maximum browser compatibility.

For example consider this embedded mp4 video:

```
{{video.mp4|A funny video}}
```

Last update: 2021/03/19 14:27

When you upload a video.webm and video.ogv next to the referenced video.mp4, DokuWiki will automatically add them as alternatives so that one of the three files is understood by your browser.

Additionally DokuWiki supports a "poster" image which will be shown before the video has started. That image needs to have the same filename as the video and be either a jpg or png file. In the example above a video.jpg file would work.

Lists

Dokuwiki supports ordered and unordered lists. To create a list item, indent your text by two spaces and use a * for unordered lists or a - for ordered ones.

- This is a list
- The second item
 - You may have different levels
- Another item
- 1. The same list but ordered
- 2. Another item
 - 1. Just use indention for deeper levels
- 3. That's it
- * This is a list
- * The second item
 - * You may have different levels
- * Another item
- The same list but ordered
- Another item
 - Just use indention for deeper levels
- That's it

Also take a look at the FAQ on list items.

Text conversions

DokuWiki can convert certain pre-defined characters or strings into images or other text or HTML.

The text to image conversion is mainly done for smileys. And the text to HTML conversion is used for typography replacements, but can be configured to use other HTML as well.

Text to image conversions

DokuWiki converts commonly used Wemoticons to their graphical equivalents. Those Smileys and other images can be configured and extended. Here is an overview of Smileys included in DokuWiki:

• 😊 8-)

- 🥸 8-0
- 🙁 :-(
- 😛 :-)
- U =)
- 🙄 :-/
- 😕 :-\
- 😃 :-?
- 😛 :-D
- 🔐 :-P
- 🙂 :-0
- O
- 🧐 :-X
- 😐 :-|
- 😉 ;-)
- 😉 ^ ^
- ?:
- 🕛 :!:
- 👙 LOL
- Fix Me! FIXME

Text to HTML conversions

Typography: DokuWiki can convert simple text characters to their typographically correct entities. Here is an example of recognized characters.

```
\rightarrow \leftarrow \leftrightarrow \Rightarrow \Leftarrow \Leftrightarrow  » « – — 640×480 © ^{\text{TM}} ® "He thought 'It's a man's world'..."
```

```
-> <- <-> => <= <=> >> << -- --- 640x480 (c) (tm) (r) "He thought 'It's a man's world'..."
```

The same can be done to produce any kind of HTML, it just needs to be added to the spattern file.

There are three exceptions which do not come from that pattern file: multiplication entity (640×480), 'single' and "double quotes". They can be turned off through a **sconfig option**.

Quoting


Some times you want to mark some text to show it's a reply or comment. You can use the following syntax:

```
I think we should do it
> No we shouldn't
>> Well, I say we should
> Really?
```

Last update: 2021/03/19 14:27

```
>> Yes!
>>> Then lets do it!
```

I think we should do it



Tables

DokuWiki supports a simple syntax to create tables.

Heading 1	Heading 2	Heading 3
Row 1 Col 1	Row 1 Col 2 Row 1 Col 3	
Row 2 Col 1	some colspan (not	e the double pipe)
Row 3 Col 1	Row 3 Col 2	Row 3 Col 3

Table rows have to start and end with a | for normal rows or a ^ for headers.

To connect cells horizontally, just make the next cell completely empty as shown above. Be sure to have always the same amount of cell separators!

Vertical tableheaders are possible, too.

	Heading 1	Heading 2
Heading 3	Row 1 Col 2	Row 1 Col 3
Heading 4	no colspan this time	
Heading 5	Row 3 Col 2	Row 3 Col 3

As you can see, it's the cell separator before a cell which decides about the formatting:

I	^ Heading 1	^ Heading 2	^
^ Heading 3	Row 1 Col 2	Row 1 Col 3	I
^ Heading 4	no colspan this time	1	I
^ Heading 5	Row 3 Col 2	Row 3 Col 3	I

You can have rowspans (vertically connected cells) by adding ::: into the cells below the one to which they should connect.

Heading 1	Heading 2	Heading 3
Row 1 Col 1	this cell spans vertically	Row 1 Col 3
Row 2 Col 1		Row 2 Col 3
Row 3 Col 1		Row 3 Col 3

Apart from the rowspan syntax those cells should not contain anything else.

^ Heading 1	^ Heading 2	^ Heading 3	^	
Row 1 Col 1	this cell spans v	ertically Row 1 Col 3	1	
Row 2 Col 1	:::	Row 2 Col 3		
Row 3 Col 1	:::	Row 3 Col 3		

You can align the table contents, too. Just add at least two whitespaces at the opposite end of your text: Add two spaces on the left to align right, two spaces on the right to align left and two spaces at least at both ends for centered text.

Table with alignment		
right center left		
left	right	center
xxxxxxxxx	xxxxxxxxxx	xxxxxxxxxx

This is how it looks in the source:

^ Table with alignment	^^^
right center left	
left right center	
xxxxxxxxxxx xxxxxxxxxxxx xxxxxxxx	xx

Note: Vertical alignment is not supported.

No formatting

If you need to display text exactly like it is typed (without any formatting), enclose the area either with <nowiki> tags or even simpler, with double percent signs %%.

This is some text which contains addresses like this: http://www.splitbrain.org and **formatting**, but nothing is done with it. The same is true for // this text// with a smiley ;-).

```
<nowiki>
This is some text which contains addresses like this:
http://www.splitbrain.org and **formatting**, but nothing is done with it.
</nowiki>
The same is true for %%//__this___ text// with a smiley ;-)%.
```

Code blocks

You can include code blocks into your documents by either indenting them by at least two spaces (like used for the previous examples) or by using the tags <code> or <file>.

```
This is text is indented by two spaces.

This is preformatted code all spaces are preserved: like <-this
```

This is pretty much the same, but you could use it to show that you quoted a file.

Those blocks were created by this source:

Syntax highlighting

DokuWiki can highlight sourcecode, which makes it easier to read. It uses the GeSHi Generic Syntax Highlighter – so any language supported by GeSHi is supported. The syntax uses the same code and file blocks described in the previous section, but this time the name of the language syntax to be highlighted is included inside the tag, e.g. <code java> or <file java>.

```
/**
 * The HelloWorldApp class implements an application that
 * simply displays "Hello World!" to the standard output.
 */
class HelloWorldApp {
    public static void main(String[] args) {
        System.out.println("Hello World!"); //Display the string.
    }
}
```

The following language strings are currently recognized: 4cs, 6502acme, 6502kickass, 6502tasm, 68000devpac, abap, actionscript3, actionscript, ada, aimms, algol68, apache, applescript, apt_sources, arm, asm, asp, asymptote, autoconf, autohotkey, autoit, avisynth, awk, bascomavr, bash, basic4gl, batch, bf, biblatex, bibtex, blitzbasic, bnf, boo, caddcl, cadlisp, ceylon, cfdg, cfm, chaiscript, chapel, cil, c_loadrunner, clojure, c_mac, cmake, cobol, coffeescript, c, cpp, cpp-qt, cpp-winapi, csharp, css, cuesheet, c_winapi, dart, dcl, dcpu16, dcs, delphi, diff, div, dos, dot, d,

ecmascript, eiffel, email, epc, e, erlang, euphoria, ezt, f1, falcon, fo, fortran, freebasic, freeswitch, fsharp, gambas, gdb, genero, genie, gettext, glsl, gml, gnuplot, go, groovy, gwbasic, haskell, haxe, hicest, hq9plus, html, html4strict, html5, icon, idl, ini, inno, intercal, io, ispfpanel, java5, java, javascript, jcl, j, jquery, julia, kixtart, klonec, klonecpp, kotlin, latex, lb, ldif, lisp, llvm, locobasic, logtalk, lolcode, lotusformulas, lotusscript, lscript, lsl2, lua, m68k, magiksf, make, mapbasic, mathematica, matlab, mercury, metapost, mirc, mk-61, mmix, modula2, modula3, mpasm, mxml, mysql, nagios, netrexx, newlisp, nginx, nimrod, nsis, oberon2, objc, objeck, ocaml-brief, ocaml, octave, oobas, oorexx, oracle11, oracle8, oxygene, oz, parasail, parigp, pascal, pcre, perl6, perl, per, pf, phix, php-brief, php, pic16, pike, pixelbender, pli, plsql, postgresql, postscript, povray, powerbuilder, powershell, proftpd, progress, prolog, properties, providex, purebasic, pycon, pys60, python, qbasic, qml, q, racket, rails, rbs, rebol, reg, rexx, robots, roff, rpmspec, rsplus, ruby, rust, sas, sass, scala, scheme, scilab, scl, sdlbasic, smalltalk, smarty, spark, sparql, sql, sshconfig, standardml, stonescript, swift, systemverilog, tclegg, tcl, teraterm, texgraph, text, thinbasic, tsql, twig, typoscript, unicon, upc, urbi, uscript, vala, vbnet, vb, vbscript, vedit, verilog, vhdl, vim, visualfoxpro, visualprolog, whitespace, whois, winbatch, wolfram, xbasic, xml, xojo, xorg conf, xpp, yaml, z80, zxbasic.

There are additional sadvanced options available for syntax highlighting, such as highlighting lines or adding line numbers.

Downloadable code blocks

When you use the <code> or <file> syntax as above, you might want to make the shown code available for download as well. You can do this by specifying a file name after language code like this:

```
<file php myexample.php>
</php echo "hello world!"; ?>
</file>
```

myexample.php

```
<?php echo "hello world!"; ?>
```

If you don't want any highlighting but want a downloadable file, specify a dash (-) as the language code: <code - myfile.foo>.

Embedding HTML and PHP

You can embed raw HTML or PHP code into your documents by using the <html> or <php> tags. (Use uppercase tags if you need to enclose block level elements.)

HTML example:

```
<html>
This is some <span style="color:red;font-size:150%;">inline HTML</span>
</html>
<HTML>
```

```
And this is some block HTML
</HTML>
```

This is some inline HTML

```
And this is some block HTML
```

PHP example:

```
<php>
echo 'The PHP version: ';
echo phpversion();
echo ' (generated inline HTML)';
</php>
<PHP>
echo 'The same, but inside a block level
element:';
echo '';
echo '';
echo '';
echo '';
echo '';
</PHP>
```

echo 'The PHP version: '; echo phpversion(); echo ' (inline HTML)';

```
echo 'The same, but inside a block level
element:';
echo '', phpversion().'';
echo '';
```

Please Note: HTML and PHP embedding is disabled by default in the configuration. If disabled, the code is displayed instead of executed.

RSS/ATOM feed aggregation

DokuWiki can integrate data from external XML feeds. For parsing the XML feeds, SimplePie is used. All formats understood by SimplePie can be used in DokuWiki as well. You can influence the rendering by multiple additional space separated parameters:

Parameter	Description
any number	will be used as maximum number items to show, defaults to 8
reverse	display the last items in the feed first
author	show item authors names
date	show item dates
description	show the item description. If KHTML is disabled all tags will be stripped
nosort	do not sort the items in the feed
<i>n</i> [dhm]	refresh period, where $d=days$, $h=hours$, $m=minutes$. (e.g. $12h = 12 hours$).

The refresh period defaults to 4 hours. Any value below 10 minutes will be treated as 10 minutes. DokuWiki will generally try to supply a cached version of a page, obviously this is inappropriate when

the page contains dynamic external content. The parameter tells DokuWiki to re-render the page if it is more than *refresh period* since the page was last rendered.

By default the feed will be sorted by date, newest items first. You can sort it by oldest first using the reverse parameter, or display the feed as is with nosort.

Example:

{{rss>http://slashdot.org/index.rss 5 author date 1h }}

- Axolotl Discovery Brings Us Closer Than Ever To Regrowing Human Limbs by BeauHD (2025/06/20 01:10)
- MIT Chemical Engineers Develop New Way To Separate Crude Oil by BeauHD (2025/06/20 00:30)
- macOS Tahoe Beta Drops FireWire Support by BeauHD (2025/06/19 23:50)
- Publishers Facing Existential Threat From AI, Cloudflare CEO Says by msmash (2025/06/19 23:10)
- Chinese Studios Plan Al-Powered Remakes of Kung Fu Classics by BeauHD (2025/06/19 22:30)

Control macros

Some syntax influences how DokuWiki renders a page without creating any output it self. The following control macros are available:

Macro	Description
~~NOTOC~~ If this macro is found on the page, no table of contents will be created	
~~NOCACHE~~	DokuWiki caches all output by default. Sometimes this might not be wanted (eg. when the <php> syntax above is used), adding this macro will force DokuWiki to rerender a page on every call</php>

Syntax Plugins

DokuWiki's syntax can be extended by **Plugins**. How the installed plugins are used is described on their appropriate description pages. The following syntax plugins are available in this particular DokuWiki installation:

- ACL Info Plugin 2020-10-01 by Andreas Gohr
 Displays information about the ACLs for the current page
- authorstats plugin 2021-02-28 by George Chatzisofroniou, Constantinos Xanthopoulos Plugin that outputs statistics about the wiki's authors.
- Cloud Plugin 2020-09-27 by Michael Hamann, Michael Klier, Gina Haeussge Displays the most used words in a word cloud.
- color syntax plugin 2018-10-12 by Harald Hanche-Olsen Write colored text in DokuWiki.
- Comment Syntax support 2021-01-01 by Satoshi Sahara
 Allow to use source comment syntax to leave edit instructions of the page. Comments are visible only in the source view, not rendered as any page elements.
- discussion plugin 2020-09-24 by Michael Hamann, Gerrit Uitslag, Gina Häussge, Christopher Smith, Michael Klier, Esther Brunner, Matthias Schulte

Last update: 2021/03/19 14:27

Provides discussion funtionality for wiki pages

 Dw2Pdf plugin 2021-02-07 by Andreas Gohr and Luigi Micco DokuWiki to PDF converter

 folded plugin 2020-09-24 by Michael Hamann, Fabian van-de-l_Isle, Christopher Smith, Esther Brunner

Foldable page sections

 fontsize2 plugin 2017-01-07 by Thorsten Stratmann DokuWiki plugin for controlling the size of your text

• Gallery Plugin 2019-01-05 by Andreas Gohr

Creates a gallery of images from a namespace or RSS/ATOM feed

• hidden Plugin 2019-03-31 by Guillaume Turri

Enable to hide/show details

• iframe plugin 2016-02-02 by Christopher Smith

Allows external URLs to be loaded into an iframe in your DokuWiki page.

• Indexmenu Plugin 2020-07-31 by Samuele Tognini

Show a customizable and sortable index for a namespace

• Info Plugin 2020-06-04 by Andreas Gohr

Displays information about various DokuWiki internals

 Navigation Plugin 2021-02-16 by Andreas Gohr Build a navigation menu from a list

 orphanswanted plugin 2017-06-25 by Doug Edmunds, Cyrille37, Federico Ariel Castagnini, Andy Webber, Matthias Schulte

Display Orphans, Wanteds and Valid link tables

- Pagelist Plugin 2020-09-27 by Matthias Schulte, Michael Hamann, Michael Klier, Gina Haeussge Lists pages in a nice formatted way
- Searchable javascript 2010-10-22 by Robert Henjes

Add <searchtable> and </searchtable> around your table.

• sortablejs 2016-05-26 by vaxquis

Allow sorting tables by columns

• Table Width Plugin 2016-10-13 by Mykola Ostrovskyy

Allows to specify width of table columns.

• Tag Plugin 2020-09-26 by Michael Hamann, Gina Häussge, Christopher Smith, Michael Klier, Esther Brunner

tag wiki pages

• ToDo 2020-06-17 by Leo Eibler, Christian Marg, Markus Gschwendt

Create a checkbox based todo list with optional user assignment (by using <todo>This is a ToDo</todo>). In combination with dokuwiki searchpattern plugin it is a lightweight task list management system.

• top plugin 2016-01-13 by Andreas Gohr show the top ten most visited pages

Video Sharing Site Plugin 2020-03-18 by Andreas Gohr

Easily embed videos from various Video Sharing sites. Example: {{youtube>XXXXXX}}}

• whoisonline plugin 2013-06-12 by Matthew Mills

Tracks who is online and where they are from

• Wrap Plugin 2018-04-22 by Anika Henke

Universal plugin which combines functionalities of many other plugins. Wrap wiki text inside containers (divs or spans) and give them a class (choose from a variety of preset classes), a width and/or a language with its associated text direction.

1)

This is a footnote.

2)

When the aspect ratio of the given width and height doesn't match that of the image, it will be cropped to the new ratio before resizing.

From:

https://wiki.allthatyouhear.com/ - allthatyouhear

Permanent link:

https://wiki.allthatyouhear.com/doku.php?id=wiki:syntax

Last update: 2021/03/19 14:27

